


LE550D


Photoelectric Sensor – Laser Scanning System



Features

- 2-digit 8-segment display
- Cable, PVC, 2 m
- Range: 100...1000 mm
- Laser class 2, red, 650 nm, acc. to IEC 60825-1:2007
- Resolution at 100 mm - 600 mm distance: < 0.5 mm
- Resolution at 600 mm - 1000 mm distance: < 1 mm
- Operating voltage: 12...30 VDC
- Two switching outputs PNP/NPN configurable


Wiring diagram



Functional principle

The LE550 laser sensors measure the distance to an object up to a range of 1 m. The settings are made via buttons at the housing. The built-in display assists with the menu navigation and is used to display the measured distance. The switching output is reprogrammable and the analog output is, depending on the type, either laid out as current or voltage output. The integrated connector is rotatable by 90° degrees which makes it easy to mount. The transmitter LED can be turned off via the menu or the grey wire (PIN 5). The same wire can be used to operate two devices in the synch mode, which prevents mutual influence. The measurement achieves an accuracy of 0.5 mm at a distance of max. 600 mm.

Excess Gain Curve



Technical data

Type	LE550D
ID no.	3094198
Optical data	
Function	Proximity switch
Operating mode	Triangulation
Light type	Red
Wavelength	650 nm
Laser class	▲ 2
Optical resolution	1 mm
Repeatability	0.5 mm
Range	100...1000 mm
Ambient light immunity	10000 lux
Electrical data	
Operating voltage	12...30 VDC
DC rated operational current	≤ 70 mA
Short-circuit protection	yes
Reverse polarity protection	yes
Output function	PNP/NPN
Output 2	Switching output
Switching frequency	≤ 250 Hz
Readiness delay	≤ 2 s
Readiness delay	≤ 2000 ms
Response time typical	< 2 ms
Mechanical data	
Design	Rectangular, LE550
Dimensions	56 x 26 x 60 mm
Housing material	Metal, Die-cast zinc alloy, Black


Technical data

Lens	plastic, Polycarbonate
Electrical connection	Cable, 2 m, PVC
Number of cores	5
Ambient temperature	-20...+55 °C
Storage temperature	-30...+65 °C
Relative humidity	90 %
Protection class	IP67
Special features	keep/defer
Power-on indication	LED, Green
Switching state	LED, Yellow
Tests/approvals	
Approvals	CE, cULus listed

Accessories

SMBLEL


3086754



Mounting bracket, rectangular, stainless steel, for side mounting of LE250/550 sensors

SMBLEFA


3088226



Mounting bracket, rotatable, stainless steel, for sensors of the LE250/550 series

SMBLEU

3086755



Protective housing, stainless steel, for sensors of the LE250/550 series