

RSSW RKS

W 458-10M

PROFIBUS Cable – PUR Cable Jacket

Features




- Jacket material: PUR
- Jacket color: purple
- Suitable for drag chain use
- UL approval
- Protection class: IP67
- M12 female, straight, reverse-keyed
- Cable length: 10 m

Technical data

Type	RSSW RKS
ID	W 458-10M
Connector A	U0398-421
Number of Pins	Male, M12 × 1, Straight, B-coded
Contacts	5
Contact carriers	Metal, CuZn, Gold-plated
Connector body	Plastic, TPU, Black
Coupling nut/screw	Plastic, TPU, Black
Tightening torque (range)	Brass, CuZn, Nickel-plated
Mechanical lifespan	0.8 ... 1 Nm (observe max. torque of mating connector!)
Pollution degree	> 100 Mating cycles
Protection class	3
Connector B	IP67, Only in screwed condition
Number of pins	Female, M12 × 1, Straight, B-coded
Contacts	5
Contact carriers	Metal, CuZn, Gold-plated
Connector body	Plastic, TPU, Black
Coupling nut/retaining screw	Plastic, PUR, Black
Seal	Brass, CuZn, Nickel-plated
Tightening torque	Plastic, FPM/FKM
Mechanical life	0.8 ... 1 Nm (observe max. torque of mating connector!)
Pollution degree	> 100 Mating cycles
Protection class	3
Cable	IP67, Only when screwed together
Network protocol	PROFIBUS-DP, 458

Cable Cross-Section



Technical data

Cable diameter	Ø 8.5 mm ±0.30
Cable length	10 m
Cable jacket	PUR, Violet
Shielding	Aluminum foil, tinned copper wire
Core insulation	PE
Core cross-section	2 x 0.34 mm ²
Arrangement of strands	65 x 0.079 mm
Core colors	GN, RD
Electrical properties at +20 °C	
Rated voltage	250 V
Current	4 A
DC resistance (loop)	50 Ω/km
Nom. impedance	150 Ω (1MHz)
Nom. capacitance	29.53 pF/m
Mechanical and chemical properties	
Bending radius (stationary installation)	≥ 5 x Ø
Bending radius (flexible use)	≥ 15 x Ø
Bending cycles	≥ 10 million
Torsional stress	± 180 °/m
Ambient temperature range (stationary)	-40...+80 °C
Ambient temperature range (In motion)	-40...+60 °C
Ambient temperature during drag chain operation	-25...+60 °C
Other Features	
Qualified for drag chain use	yes
Halogen-free	no
UV resistance	yes
Flame-retardant	yes
Approvals	UL CSA
Note	
- We reserve the right to make technical modifications without prior notice.	