


WL50SRL5


Work Light – Spotlight



Features

- Operating voltage: 12...30 VDC
- Protection class: IP69K
- Metal housing
- Color red
- Cable, 2m

Wiring diagram



Functional principle

The energy-efficient LED work lights are ideally suited for industrial applications. The rugged IP69K protected versions can be used in many demanding applications where bright and uniform illumination is required. The electrical connection is either established via standard M12x1 connector or pigtail directly at the clamp connection of existing installations. On some models the light output is continuously dimmable via a PWM signal on pin 4.

Technical data

Type	WL50SRL5
ID	3018755
Signal and display data	
Purpose	LED work light
Function	Spotlight
Light type	Red
Luminous flux lumen	110 lm
Aperture angle degree	5 °
Beam angle	5°
LED service life (L70)	50000 h
Dimmable	No
Features of color 1	Red, Permanently on, 110 lm
Special features	Wash down
Electrical data	
Operating voltage	12...30 VDC
DC rated operational current	≤ 400 mA
Input power	1.7 W
Mechanical data	
Cascadable	No
Design	Puck, WL50S
Dimensions	Ø 50 x 51 mm
Housing material	Metal, AL, Black
Window material	Polycarbonate, clear
Electrical connection	Cable, 2 m, PVC
Number of cores	2
Ambient temperature	-20...+50 °C
Storage temperature	-40...+70 °C

Technical data

Relative humidity	0...95 %
Protection class	IP67 IP69
Tests/approvals	
Approvals	CE