


WLB92ZC550PBQMC

Work Light – Linear Light



Features

- Light beam: 550 mm
- Operating voltage: 110...277 VAC
- Protection class: IP40
- Color: White
- Connection cable with open ends incl. in delivery
- Built-in ON/OFF switch
- Integrated rotary switch for continuous dimming of the light output (0% - 100%)

Functional principle


The WLB92Z LED linear light is designed for multi-purpose use, is powered by 100-277 VDC and convinces by its robust metal housing and shatter-proof window material. The light can be switched on or off with the built-in toggle switch and fully dimmed with an additional rotary switch. The color temperature lies in the range of daylight, between 5,000 and 10,000 Kelvin. With a lifetime of 50,000 hours and very energy efficient LEDs, this a cost-saving and environmentally friendly alternative to conventional fluorescent lamps. This linear light is available in two lengths and more than twice as bright as the known WLB32 LED light.

Technical data


Type	WLB92ZC550PBQMC
ID	3093263
Signal and display data	
Purpose	LED work light
Function	Linear light
Light type	White
Color temperature	4700...+5300 K
Luminous flux lumen	3130 lm
Dimmable	Potentiometer
Features of color 1	White, Permanently on, 3510 lm
Electrical data	
Operating voltage	100...277 VAC
Mechanical data	
Cascadable	Yes
Design	Rectangular, WLB92
Dimensions	665 x 97 x 104 mm
Housing material	Metal, AL, Anodized
Window material	Polycarbonate, diffuse
Electrical connection	Connector, PVC
Number of cores	3
Ambient temperature	-35...+50 °C
Protection class	IP40
Tests/approvals	
Approvals	CE

Accessories


LMBWLB92 **3093567**
 Snap bracket for WLB92 work light,
 included in the WLB92 scope of
 delivery




LMBWLB92CLIP **3093568**
 Snap bracket for WLB92 linear light




LMBWLB92HK5 **3093569**
 Pendant mounting bracket for WLB92




LMBWLB92S **3093570**
 Mounting bracket for front side
 mounting of the WLB92



LMBWLB92RAS **3093571**
 Pivoting mounting bracket for WLB92
 line light



Accessories

Dimension drawing	Type	ID	
	LQMAC-306	3086779	Connection cable, 3-wire, stranded wire
	LQMAEC-306SS	3085580	Extension cable to cascade WLB32 lights, length 1.83 m, optional